

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/032186 A2

(51) International Patent Classification:

H01L

(74) Agent: OLSON, Timothy, J.; Wiggin & Dana LLP, One Century Tower, New Haven, CT 06508-1832 (US).

(21) International Application Number:

PCT/US2003/029569

(22) International Filing Date:

23 September 2003 (23.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/415,189

30 September 2002 (30.09.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): ADVANCED INTERCONNECT TECHNOLOGIES LIMITED [MU/MU]; c/o Valmet (Mauritius) Limited, 608 St. James Court, St. Denis Street, Port Louis (MU).

Published:


— without international search report and to be republished upon receipt of that report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): LAU, Daniel, K. [US/US]; 395 Stonecrest Drive, San Francisco, CA 94312 (US). LAW, Edward, L., T. [US/US]; 925 Sunnyside Lane, Tracy, CA 95376 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THERMAL ENHANCED PACKAGE FOR BLOCK MOLD ASSEMBLY



(57) Abstract: A heat spreader (20) is added to a package to enhance thermal and advantageously electrical performance. In manufacture, a heat spreader precursor (24) is advantageously placed over a group of dies and secured after bonding (e.g., wire or tape bonding or flip-chip bonding) and before matrix/block mold. For example, a package strip (10) may consist of a row (linear array) of groups of die attach areas (e.g. in a rectangular array of four). The heat spreader precursor (20) may accommodate one such group or multiple groups along the package strip (10). The package strip (10) may then be singulated to form the individual packages. Each singulated package includes a die (14), its associated substrate 16 (e.g., either a lead frame or interposer type substrate) and a portion of the heat spreader precursor (24) as a heat spreader (20).

WO 2004/032186 A2